



LEVELWIND™

- LevelWind Technology
- Extra large swivel for best flow
- Maintainable without special tools
- Free standing base
- Durable construction
- Latching Switch
- 7 position locking brace
- Mounting bracket included
- Adjustable hose stop
- Optional mounting bracket

Retractable air / water reels with Levelwind™ Technology



model	application	hose included	hose material	connection in / out	working pressure	temperature deg C	weight
L8306-EU	Air	23m x 10mm ID	PVC	M1/4" BSPT	24 bar	10 to 65	12 kg
◆ L8306-FZ	Air	23m x 10mm ID	Flexzilla®	M1/4" NPT	20 bar	-40 to 65	12 kg
L8310-EU	Air	30m x 10mm ID	PVC	M1/4" BSPT	24 bar	10 to 65	12 kg
L8335-EU	Air / Water	15m x 13mm ID	PVC	M1/2" BSPT	20 bar	10 to 65 ■	12 kg
◆ L8335-FZ	Air	15m x 13mm ID	Flexzilla®	M3/8" NPT	20 bar	-40 to 65	12 kg
L8345	Garden	23m x 13mm ID	PVC	M1/2" BSPT	10 bar	5 to 60	12 kg
L8350	Potable Water	23m x 13mm ID	PVC	M1/2" BSPT	10 bar	5 to 60	12 kg
L8351	Marine ●	18m x 16mm ID	PVC	M1/2" BSPT	10 bar	5 to 60	15 kg



The colour CHARTREUSE as applied to the body of the air hose is a registered trademark owned by Weems Industries, Inc. Flexzilla is a registered trademark owned by Weems Industries, Inc. Levelwind is a trademark owned by Weems Industries, Inc.

- ◆ Flexzilla® Air Hose Reel featuring Levelwind™ Technology
 - 5 to 60 deg C for water application
 - With stainless steel critical components



Optional bench and high ceiling bracket available.

L8300-B

Other models available for other applications
www.bridge-engineering.co.uk